




## Hardness Testing

# Equotip Live UCI

Wireless Portable Ultrasonic Contact Impedance (UCI) Hardness Tester



### Versatility

Advanced wireless UCI system based on innovative and patented force-sensing technology enables various test loads in one probe design.



### Productivity

Extremely efficient user interface and enhanced logbook built into our constantly evolving Equotip app enables documentation through photos, voice comments, and annotations.



### User Experience

Ultra-portable UCI probe with cloud connectivity built into modern IoT ecosystem with enabled data back-up, instant evaluation, and data sharing. Access your data from anywhere, anytime.



**Display and processing unit (not included)**

<b>Display</b>	Any Apple iOS device (min. iOS 13)
<b>Instrument protection</b>	Water, dust and debris resistance and MIL grade protection achieved through an external case/sleeve of customers' choice
<b>Memory</b>	>10'000'000 measurements, limited by the storage of the iOS device

**UCI Live operating parameters**

<b>Connectivity</b>	Bluetooth LE, Micro USB for charging and service connection
<b>Battery</b>	1x AA (NiMH), flight safe
<b>Battery lifetime</b>	4-6h, > 3'000 measurements, depending on battery's capacity
<b>Charging time</b>	< 4-6h
<b>Power input</b>	5V, through micro USB
<b>Dimensions</b>	77 x 62 x 185.5 mm / 3 x 2.4 x 7.3 in
<b>Weight</b>	234 g / 8.26 oz
<b>Humidity operation</b>	< 90% RH, non-condensing
<b>Operating temperature</b>	(-) 20°C + 60°C / 14°F – 122°F
<b>Certification</b>	CE, KC, FCC

<b>Equotip App Features</b>	<ul style="list-style-type: none"> <li>- Automatic data backup to ScreenigEagle's Workspace</li> <li>- Histogram and table view, series statistics</li> <li>- Automatic conversion to selected unit</li> <li>- Probe verification assistant</li> <li>- Custom material conversion: 1-point shift</li> <li>- Voice read-out of measurement data</li> <li>- Enhanced logbook with metadata (images, voice comments, annotations, geo location)</li> <li>- Data export to pdf and CSV</li> <li>- Probe statistics</li> <li>- Video tutorials</li> </ul>
-----------------------------	--

<b>Conversion curves applicable for materials</b>	- Steel and cast steel
---	------------------------

<b>Languages</b>	English, Chinese, French, German, Italian, Japanese, Korean, Portuguese, Russian, Spanish, Turkish
------------------	--

<b>Regional settings</b>	Metric and imperial units, multi-language and time-zone
--------------------------	---

<b>Audio support</b>	Full digital audio
----------------------	--------------------

**Proceq Workspace Cloud Solution**

<b>Proceq Workspace</b>	Web-based data management system with cloud backup, accessible from PC, Mobile and Tablets.
-------------------------	---

<b>Language support</b>	English
-------------------------	---------



<b>Native Scale</b>	HV(UCI)
<b>Conversion scales</b>	HLD, HB, HRC, HRA, HRB, HR15N, HR15T MPA ( $\sigma_1$ , $\sigma_2$ , $\sigma_3$ )
<b>Measurement range</b>	20-2000 HV
<b>Indenter</b>	ISO 6507-2 compliant, 136° Vickers diamond
<b>Impact energy / Test force</b>	HV1 (9.8 N), HV5 (49 N), HV10 (98N) in one probe
<b>Accredited calibration</b>	ISO/IEC 17025
<b>Standard compliance</b>	ASTM A1038 DIN 50159 GB/T 34205
<b>Guidelines</b>	ASME CRTD-91 ASTM A370 DGZfP Guideline MC 1 VDI / VDE Guideline 2616 Paper 1
<b>Conversion standards</b>	ASTM E140 ISO 18265 Proceq's own conversion curves
<b>Measurement resolution</b>	1 HV(UCI), 0.1 HRC
<b>Measuring accuracy</b>	± 2%
<b>Measurement deviation (E)</b>	Lower than DIN 50159 & GB/T 34205
<b>Coefficient of variation (R)</b>	Lower than DIN 50159 & GB/T 34205
<b>Weight</b>	234 g / 8.26 oz
<b>Dimensions</b>	77 x 62 x 185.5 mm / 3 x 2.4 x 7.3 in



Standards & Guidelines	Description
ASTM A 1038	
ASTM A 370	
ASTM E 140	
DIN 50159	
GB/T 34205-2017	
ISO 18265	
ASME CRTD-91	
DGZfP Guideline MC 1	
VDI / VDE Guideline 2616 Paper 1	



Present in +100 countries, we serve inspectors and engineers all over the world with the most comprehensive range of InspectionTech solutions, combining intuitive software and Swiss-manufactured sensors.  
[www.screeningeagle.com](http://www.screeningeagle.com)

