

## Proceq Ground Penetrating Radars

# GP8100

---

Highly productive portable concrete GPR array, enabling quick object detection and superior data collection

---



### Productivity

Boost scanning efficiency with 25cm effective scan width and 80cm penetration depth, one scan is equivalent to 6 classical line scans



### Visualization

Detecting objects of all sizes and marking on concrete surfaces has never been so easy and fast with the superline scan view



### Density

The high scan rate of 1'200 scans/s enables a very dense GPR data collection in only one superline scan, which can be visualized in 6 classical line scans




## Proceq GPR App Tech Specs

<b>Measurement modes</b>	Superline Scan (1000m / 3281 ft) Area Scan (with Flexible Grid up to 100m2 / 1076 ft2)
<b>Review modes</b>	Superline scan <sup>1</sup> A-scan (incl. envelope) Migrated view Non-migrated view Split view <sup>1</sup> Time-Slice view <sup>2</sup> Basic 3D view AR
<b>Advanced visualization</b>	Time-Slice view Pro 3D view Augmented Reality (AR)
<b>Reporting</b>	Workspace integration Automatic Logbook SEG-Y export Instant report generation Share via URL
<b>Export formats</b>	JPG PNG CSV SEGY HTML
<b>Display Unit Specs*</b>	Latest Apple® iPad recommended (iPad with iOS 11.0 and higher) Screen size: From 7.9" to 12.9" Resolution: Up to 2732-by-2048 Memory: Up to 2TB Weight: Down to 301 g / 10.6 oz Camera: Up to 12MP Wide and 10MP Ultra Wide Optional: USB-C, 5G, Face ID
<b>Display Unit Sensors*</b>	LiDAR Scanner (optional) Three-axis gyro Accelerometer Ambient light sensor Barometer Built-in GPS/GNSS

1. GP8100 only; 2. GP8000 & GP8100 only

\* Depending on iPad model





## Instrument Tech Specs

<b>Radar technology</b>	Stepped-frequency continuous-wave (SFCW) GPR
<b>Modulated frequency range</b>	400 – 4000 MHz
<b>Penetration depth</b>	80 cm / 31.5 in
<b>Battery</b>	Flight-safe, removable pack, 8x AA (NiMH)
<b>Dimensions</b>	41.5 x 22.5 x 13.2 cm 16.3 x 8.9 x 5.2 in
<b>Weight</b>	3.0 kg / 6.6 lbs (excl. battery pack)
<b>Ground clearance</b>	0.8 cm / 0.32 in
<b>Antennas</b>	6
<b>Antenna distance to edge</b>	8.3 cm / 3.27 in
<b>Special features</b>	All-wheel drive with high-traction wheels and laser light guidance USB-C tethering to power bank
<b>Connections</b>	Wi-Fi (802.11n) to display unit USB-C for Wi-Fi restricted areas
<b>Autonomy</b>	3h (Up to 8 hours with off-the-shelf 10'000 mAh power bank, not included)



## Our Accessories

Image	PartNumber	Description
	79330235	Universal tablet holder for direct mounting on Proceq GPR 8000/8100 and Pundit PD8050
	39380010	Telescopic rod kit for Proceq GPR instruments including the universal tablet holder UTH100 Compatible with GP8000, GP8100 and GP8800...
	79330345	Chest harness kit for hands free operation of all iPad app based instruments: GP8000, GP8100, GP8800, PD8050, PM8000, PI8000...
	39222010	Telescopic rod kit for Profometer PM8000 instruments including the universal tablet holder UTH100

Standards & Guidelines	Description
ACI 228.2R.98	
ASTM D4748-10	
ASTM D6087-08	
ASTM D6432-11	
EN 302066 - ETSI	
NCHRP Synesis 255	
SHRP H-672	
SHRP S-300	
SHRP S-325	

SWISS  MADE



Present in +100 countries, we serve inspectors and engineers all over the world with the most comprehensive range of InspectionTech solutions, combining intuitive software and Swiss-manufactured sensors.  
[www.screeningeagle.com](http://www.screeningeagle.com)

[Request a quote](#)



Machine translated & automatically generated (English version prevails): 14.05.2024  
 Copyright © 2023 Screening Eagle Technologies AG or its affiliates. All rights reserved.

