



## Automatic film applicators

# ZAA2600.A

---

Automatic Film Applicator with Capacitive Touchscreen

---




### User experience

Multi-language menu guidance on the touch screen with storage of various application profile settings such as application length and drawing speed.



### Reliability

Reproducible, operator-independent results allow for storage of various application profile settings such as application length and drawing speed.



### Versatility

Thanks to its modular construction and compact design, it can be equipped with different kits for applications like scrub resistance, washability, crocking, and scratch resistance tests.



## Instrument Tech Specs

<b>Display</b>	Touchscreen 5.7" colour TFT (LCD), LED backlight, VGA resolution
<b>Measuring Area</b>	Application length: up to 400 mm (15.75") Application width: up to 300 mm (11.81")
<b>Weight</b>	2600.A: ≈ 20 kg (≈ 44.1 lbs) Glass plate only: 6.4 kg (14.1 lbs)
<b>Battery</b>	Power supply: 100 V - 240 V, 50 Hz - 60 Hz
<b>Operating Temperature</b>	Temperature range Ambient conditions for operation: 5°C to +45°C (41 °F to 113 °F) Relative humidity: 20% to 80%, no condensation
<b>Special Features</b>	Drawing speed: 1 - 500 mm/s (0.04 - 19.69"/s) Resolution: 1 mm/s (0.04"/s)



Standards & Guidelines	Description
ASTM D1640 (Depending on accessory)	
ASTM D4748-10	
ASTM D6279	
ASTM D823 (Depending on accessory)	

---

SWISS  MADE

---



Present in +100 countries, we serve inspectors and engineers all over the world with the most comprehensive range of InspectionTech solutions, combining intuitive software and Swiss-manufactured sensors.  
[www.screeningeagle.com](http://www.screeningeagle.com)

[Request a quote](#)



