



Automatic film applicators

ZAA2600.A

Automatic Film Applicator with Capacitive Touchscreen




User experience

Multi-language menu guidance on the touch screen with storage of various application profile settings such as application length and drawing speed.



Reliability

Reproducible, operator-independent results allow for storage of various application profile settings such as application length and drawing speed.



Versatility

Thanks to its modular construction and compact design, it can be equipped with different kits for applications like scrub resistance, washability, crocking, and scratch resistance tests.



Instrument Tech Specs

| | |
|------------------------------|--|
| Display | Touchscreen 5.7" colour TFT (LCD), LED backlight, VGA resolution |
| Measuring Area | Application length: up to 400 mm (15.75") Application width: up to 300 mm (11.81") |
| Weight | 2600.A: ≈ 20 kg (≈ 44.1 lbs) Glass plate only: 6.4 kg (14.1 lbs) |
| Battery | Power supply: 100 V - 240 V, 50 Hz - 60 Hz |
| Operating Temperature | Temperature range Ambient conditions for operation: 5°C to +45°C (41 °F to 113 °F) Relative humidity: 20% to 80%, no condensation |
| Special Features | Drawing speed: 1 - 500 mm/s (0.04 - 19.69"/s) Resolution: 1 mm/s (0.04"/s) |



| Standards & Guidelines | Description |
|-------------------------------------|-------------|
| ASTM D1640 (Depending on accessory) | |
| ASTM D4748-10 | |
| ASTM D6279 | |
| ASTM D823 (Depending on accessory) | |

SWISS  MADE



Present in +100 countries, we serve inspectors and engineers all over the world with the most comprehensive range of InspectionTech solutions, combining intuitive software and Swiss-manufactured sensors.
www.screeningeagle.com

[Request a quote](#)



