



Automatic film applicators

**ZAA2600.C**

---

Linear abrasion tester for rubbing tests

---




### User experience

The easy-to-use touchscreen with multi-language menu guidance saves you time in the laboratory and streamlines the entire testing process



### Efficiency

Storage of various crockmeter profile settings such as stroke length and number of cycles



### Reliability

Stable and ergonomic design guarantees longevity and reliable results



## Instrument

### Tech Specs

Display	Touchscreen 5.7" colour TFT (LCD), LED backlight, VGA resolution
Weight	Up to 4.5 kg (9.92 lbs) can be applied
Drawing speed	1 - 500 mm/s (0.04 - 19.69"/s), stepless adjustability
Resolution	Resolution: 1 mm/s (0.04"/s)

Standards & Guidelines	Description
AATCC method 8-2007 (Depending on accessory)	
ASTM D6279 (Depending on accessory)	
ASTM F1319 (Depending on accessory)	
DIN 55654 (Depending on accessory)	
DIN EN 13523-11 (Depending on accessory)	
EN ISO 105-X12 (Depending on accessory)	

SWISS  MADE



Present in +100 countries, we serve inspectors and engineers all over the world with the most comprehensive range of InspectionTech solutions, combining intuitive software and Swiss-manufactured sensors.  
[www.screeningeagle.com](http://www.screeningeagle.com)

[Request a quote](#)



Machine translated & automatically generated (English version prevails): 13.03.2024  
 Copyright © 2023 Screening Eagle Technologies AG or its affiliates. All rights reserved.

