



Automatic film applicators

ZAA2600.C

Linear abrasion tester for rubbing tests




User experience

The easy-to-use touchscreen with multi-language menu guidance saves you time in the laboratory and streamlines the entire testing process



Efficiency

Storage of various crockmeter profile settings such as stroke length and number of cycles



Reliability

Stable and ergonomic design guarantees longevity and reliable results



Instrument Tech Specs

Display	Touchscreen 5.7" colour TFT (LCD), LED backlight, VGA resolution
Weight	Up to 4.5 kg (9.92 lbs) can be applied
Drawing speed	1 - 500 mm/s (0.04 - 19.69"/s), stepless adjustability
Resolution	Resolution: 1 mm/s (0.04"/s)



Standards & Guidelines	Description
AATCC method 8-2007 (Depending on accessory)	
ASTM D6279 (Depending on accessory)	
ASTM F1319 (Depending on accessory)	
DIN 55654 (Depending on accessory)	
DIN EN 13523-11 (Depending on accessory)	
EN ISO 105-X12 (Depending on accessory)	

SWISS  MADE



Present in +100 countries, we serve inspectors and engineers all over the world with the most comprehensive range of InspectionTech solutions, combining intuitive software and Swiss-manufactured sensors.
www.screeningeagle.com

Request a quote



