



## Automatic film applicators

# ZAA2600.SW

---

Linear abrasion tester for wet abrasion, scrub resistance, washability and crocking tests

---



### User experience

The easy-to-use touchscreen with multi-language menu guidance saves you time in the laboratory and streamlines the entire testing process



### Efficiency

Storage of various profile settings such as stroke length and number of cycles



### Reliability

Modular and flexible design allow easy change of application



## Instrument Tech Specs

<b>Material housing</b>	Anodised aluminium
<b>Weight</b>	≈20 kg (≈44.1 lbs)
<b>Display</b>	Touchscreen 5.7" colour TFT (LCD), LED backlight, VGA resolution
<b>Test Weight</b>	Up to 4.5 kg (9.92 lbs) can be applied
<b>Stroke Length</b>	1 - 320 mm (0.04 - 12.60"), stepless adjustability
<b>Stroke Speed</b>	1 - 600 mm/s (0.04 - 23.62"/s) and up to 100 double strokes per minute respectively
<b>Power supply</b>	100 V - 240 V, 50 Hz - 60 Hz
<b>Resolution</b>	Resolution: 1 mm/s (0.04"/s)



Standards & Guidelines	Description
ASTM D2486 (Depending on accessory)	
ASTM D3450 (Depending_on_accessory)	
ASTM D4213 (Depending_on_accessory)	
ASTM D4748-10	
ASTM D4828 (Depending_on_accessory)	
JIS K 5600-5-11 (Depending on accessory)	

SWISS  MADE



Present in +100 countries, we serve inspectors and engineers all over the world with the most comprehensive range of InspectionTech solutions, combining intuitive software and Swiss-manufactured sensors.  
[www.screeningeagle.com](http://www.screeningeagle.com)

Request a quote



