



Automatic film applicators

ZAA2600.SW

Linear abrasion tester for wet abrasion, scrub resistance, washability and crocking tests



User experience

The easy-to-use touchscreen with multi-language menu guidance saves you time in the laboratory and streamlines the entire testing process



Efficiency

Storage of various profile settings such as stroke length and number of cycles



Reliability

Modular and flexible design allow easy change of application



Instrument Tech Specs

Material housing	Anodised aluminium
Weight	≈20 kg (≈44.1 lbs)
Display	Touchscreen 5.7" colour TFT (LCD), LED backlight, VGA resolution
Test Weight	Up to 4.5 kg (9.92 lbs) can be applied
Stroke Length	1 - 320 mm (0.04 - 12.60"), stepless adjustability
Stroke Speed	1 - 600 mm/s (0.04 - 23.62"/s) and up to 100 double strokes per minute respectively
Power supply	100 V - 240 V, 50 Hz - 60 Hz
Resolution	Resolution: 1 mm/s (0.04"/s)



Standards & Guidelines	Description
ASTM D2486 (Depending on accessory)	
ASTM D3450 (Depending_on_accessory)	
ASTM D4213 (Depending_on_accessory)	
ASTM D4748-10	
ASTM D4828 (Depending_on_accessory)	
JIS K 5600-5-11 (Depending on accessory)	

SWISS  MADE



Present in +100 countries, we serve inspectors and engineers all over the world with the most comprehensive range of InspectionTech solutions, combining intuitive software and Swiss-manufactured sensors.
www.screeningeagle.com

Request a quote



