



Profometer Rebar Diameter & Cover Meter

PM8000 Lite

The durable concrete cover meter for easy rebar location, finding safe spots to drill and fast quality checks by reading rebar cover & diameter measurements



Precision

Designed and produced in Switzerland for highest quality and performance for professional rebar detection



Ergonomics

Compact, ultra light-weight, and ergonomically designed for use in rough environments and to fit comfortably in one hand



Simplicity

Find your rebars, safe spots to drill, determine the covers and estimate the diameter with precision and clear results



Measurement Modes	Spot data import			
Review Modes	Statistics			
Display settings	Concrete cover threshold slider with colour palette			
On-site annotations	Photos geolocation voice notes			
Reporting	Workspace integration Share via URL Automatic Logbook Raw data export Instant report generation			
Export formats	JPG (Screenshot) PNG CSV HTML			
Display Unit Specs**:	Latest Apple® iPad recommended (iPad with iOS 13.0 and higher) Screen size: From 7.9" to 12.9" Resolution: Up to 2732-by-2048 Memory: Up to 27B Weight: Down to 301 g / 10.6 oz Camera: Up to 12MP Wide and 10MP Ultra Wide Optional: USB-C, 5G, Face ID			
Display Unit Sensors**:	LiDAR Scanner (optional) Three-axis gyro Accelerometer Ambient light sensor Barometer Built-in GPS/GNSS			

^{*} PM8000 Pro only

^{**} Depending on iPad model iPad is a trademark of Apple Inc.; iOS is a registered trademark of Cisco in the US and is used by Apple under license





Applications	Rebar location, finding safe spots to drill, quality check, minimum cover check, metal detection			
Technology	Eddy-current			
Cover Measuring depth	Up to 185 mm / 7.3 in			
Cover Measuring Accuracy	+/-1 mm / 0.04 in to 4 mm /0.16 in depending on depth			
Rebar Diameter Measuring Depth	up to 63 mm / 2.5 in			
Rebar Diameter Measuring Accuracy	+/- rebar size			
Display	High-contrast OLED screen offering vivid clarity in any light, from bright sun to darkness Intuitive navigation menu with access to all essential settings			
Dimensions	190 x 75 x 45 mm / 7.5 x 3.0 x 1.8 in			
Weight	300 g / 0.7 lb			
Battery	2 x AA (NiMH) rechargeable or non rechargeable Removable Flight-safe 8 hours autonomy USB-C power bank (not included)			

Our Accessories

Image	PartNumber	Description
4	39222010	Telescopic rod kit for Profometer PM8000 instruments including the universal tablet holder UTH100
B	79330345	Chest harness kit for hands free operation of all iPad app based instruments: GP8000, GP8100, GP8800, PD8050, PM8000, Pl8000

Standards & Guidelines	Description
BS 1881, Part 204	
DGZfP B2	
DIN 1045	
SIA 262-1	
SN 505262	
SS 78-B4	
DBV Guidelines	





Present in +100 countries, we serve inspectors and engineers all over the world with the most comprehensive range of InspectionTech solutions, combining intuitive software and Swiss-manufactured sensors.

www.screeningeagle.com

Request a quote



