

## Schmidt Rebound Hammers

# Schmidt OS-120

---


Pendulum hammer for testing on softer material such as lightweight concrete, gypsum boards, fresh concrete and mortar used for brickwork joints

---



### Resolution & depth

Only rebound hammer that provides a test result at compressive strengths below 5 Mpa.




### Versatility

Large, half-circular scale with high resolution.



### User Experience

Two models for fresh concrete and mortar applications.



## Instrument Tech Specs

Impact Energy	0.833 Nm
Compressive Strength Range	1 to 5 N/mm <sup>2</sup> (145 to 725 psi)
Display	Mechanical display



Standards & Guidelines	Description
Austrian Guideline for tunnel lining, published December 2012. Austrian Construction Association	
TNO Report BI -88-009/61.8.2060-VOE from IBBC Delft Netherlands (Mortar joint testing)	

SWISS  MADE



Present in +100 countries, we serve inspectors and engineers all over the world with the most comprehensive range of InspectionTech solutions, combining intuitive software and Swiss-manufactured sensors.  
[www.screeningeagle.com](http://www.screeningeagle.com)

[Request a quote](#)



Machine translated & automatically generated (English version prevails): 13.03.2024  
Copyright © 2023 Screening Eagle Technologies AG or its affiliates. All rights reserved.

